

12

WALL PANEL THICKNESS

2"

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] SPACED 1 1/2" FROM PANEL SEAMS, W/ INTERIOR FASTENERS CENTERED OVER MINOR RIBS (7" O.C. MAX.) (NO FASTENER @ PANEL SEAM)

HIGH SLIDING CLIP [HW-2104]

1/4-14 x 1 SELF-DRILLER W/WASHER [FASTENER #1] (2) PER CLIP

ULTRA-DEK PANEL

TRI-BEAD TAPE SEALER [HW-504]

URETHANE SEALANT [HW-54\_] @ CLOSURE ENDS/PANEL RIB & LAPPING CLOSURE TABS TO SEAL ALL VOIDS

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] (3) PER PANEL

OUTSIDE CLOSURE [HW-430] 24" PANEL [HW-432] 18" PANEL [HW-442] 12" PANEL

BACKUP PLATE [HW-7760] 24" PANEL [HW-7769] 18" PANEL [HW-7761] 12" PANEL

E.H. = ?'-?'"

1 3/8"

1" MIN.

EAVE STRUT

NOTE:  
REFERENCE TYPICAL TRIM LAP SECTIONS

SCULPTURED HIGH EAVE TRIM [FL-265]

TRI-BEAD TAPE SEALER [HW-504]

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] @ PRE-PUNCHED HOLES (6) PER 24" PANEL (5) PER 18" PANEL (4) PER 12" PANEL

12-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #3]

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] @ 12" O.C.

OUTSIDE CLOSURE

WALL PANEL

O/O DIMENSION  
(SEE PLAN)

