

NOTE:
REFERENCE TYPICAL TRIM
LAP SECTIONS

DIM
(6" MAX./2" MIN.)

NO
FASTENERS

FLEXIBLE MEMBRANE
SLIP JOINT TRIM
TRI-BEAD TAPE SEALER
[HW-504] EA. SIDE OF
FLEXIBLE MEMBRANE
1/4-14 x 1 1/4 LONG-LIFE
SELF-DRILLER W/WASHER
[FASTENER #1E] @ 24" O.C.
BATTENLOK HS PANEL
(FIELD CUT AND BEND
UP 2" LEG AS REQ'D)

TRI-BEAD TAPE SEALER [HW-504]
EA. SIDE OF FLEXIBLE MEMBRANE
HIGH WIND PARAPET RAKE
CLEAT [F292]
1/4-14 x 1 1/4 LONG-LIFE
SELF-DRILLER W/WASHER
[FASTENER #1E] @ 24" O.C.
BATTENLOK HS PANEL
(FIELD CUT AND BEND
UP 2" LEG AS REQ'D)

LOW FLOATING CLIP
[HW-220]
BEARING PLATE
[HW-7500]

DECK SCREW (2) PER CLIP
(MIN. 3/4" PENETRATION
INTO METAL DECK)

2 x 4 x 16 GA. ANGLE
DECK SCREW @ 24" O.C.
(MIN. 3/4" PENETRATION
INTO METAL DECK)

LOW RAKE SUPPORT
[HW-7712]
1/4-14 x 1 1/4 SHOULDER
TEK 2 SELF-DRILLER
[FASTENER #5] @ 24" O.C.
(CENTER IN SLOT)

RIGID INSULATION
(NOT BY MBCI)
VAPOR BARRIER
(NOT BY MBCI)
METAL DECK
(NOT BY MBCI)

3/8"

