



WALL PANEL THICKNESS

2"

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] SPACED 1 1/2" FROM PANEL SEAMS, W/ INTERIOR FASTENERS CENTERED OVER MINOR RIBS (7" O.C. MAX.) (NO FASTENER @ PANEL SEAM)

URETHANE SEALANT [HW-54\_] @ CLOSURE ENDS/PANEL RIB & LAPPING CLOSURE TABS TO SEAL ALL VOIDS

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] (3) PER PANEL

METAL OUTSIDE CLOSURE [HW-430] 24" PANEL [HW-432] 18" PANEL [HW-442] 12" PANEL

BACK-UP PLATE [HW-7760] 24" PANEL [HW-7769] 18" PANEL [HW-7761] 12" PANEL

E.H. = ?'-?"

TRI-BEAD TAPE SEALER [HW-504]

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] @ PRE-PUNCHED HOLES (6) PER 24" PANEL (5) PER 18" PANEL (4) PER 12" PANEL

SCULPTURED HIGH EAVE TRIM [FL-\_\_\_\_\_]

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] @ 12" O.C.

OUTSIDE CLOSURE

WALL PANEL

TRI-BEAD TAPE SEALER [HW-504]  
LOW SLIDING CLIP [HW-2102]  
BEARING PLATE [HW-7500]

ULTRA-DEK PANEL

12

3/8"

1" MIN.

RIGID INSULATION (NOT BY MBCI)  
VAPOR BARRIER (NOT BY MBCI)  
METAL DECK (MIN. GAUGE THICKNESS) (NOT BY MBCI)

14-10 x \_\_\_\_\_ DECK SCREW [FASTENER #15\_] (2) PER CLIP (MIN. 3/4" PENETRATION INTO METAL DECK)

NOTE: REFERENCE TYPICAL TRIM LAP SECTIONS

0/0 DIMENSION (SEE PLAN)