



URETHANE SEALANT MUST COME IN CONTACT WITH TAPE SEALER TO FORM A WEATHERTIGHT SEAL

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] @ 16" O.C.

BOX PANEL CAP TRIM [FL-272]

SCULPTURED EAVE TRIM [FL-253]

1/8 x 3/16 POP RIVET [FASTENER #14] @ 3'-0" O.C.

12-24 x 1 1/4 LONG-LIFE TEK 4.5 W/WASHER [FASTENER #78]

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] @ 12" O.C.

OUTSIDE CLOSURE
WALL PANEL

VARIES W/
ROOF SLOPE

WALL PANEL THICKNESS

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] (5) PER 16" PANEL (4) PER 12" PANEL

URETHANE TUBE SEALANT BETWEEN PANEL RIBS

TRI-BEAD TAPE SEALER [HW-504]

12

SUPERLOK PANEL

3/8"

3" x 5" x 14 GA. BENT PLATE (HOLD TOP OF PLATE 3/8" ABOVE TOP OF RIGID INSULATION)

1/8 x 3/8 POP RIVET [FASTENER #14A] @ 5'-0" O.C.

12-24 x 1 1/2 PAN HEAD TEK 4.5 SELF-DRILLER [FASTENER #16] @ 12" O.C.

STRUCTURAL ANGLE (NOT BY MBCI)

RIGID INSULATION (NOT BY MBCI)

VAPOR BARRIER (NOT BY MBCI)

METAL DECK (NOT BY MBCI)

NOTE: REFERENCE TYPICAL TRIM LAP SECTIONS

O/O DIMENSION (SEE PLAN)