



FLEXIBLE MEMBRANE
 TRI-BEAD TAPE SEALER [HW-504] EA. SIDE OF FLEXIBLE MEMBRANE
 1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] @ 24" O.C.
 SUPERLOK PANEL (FIELD CUT & BEND UP 2" LEG IF REQ'D. TO FIT AGAINST RAKE SUPPORT ANGLE)

DIM. (6" MAX./2" MIN.)
 NO FASTENERS

TRI-BEAD TAPE SEALER [HW-504] EA. SIDE OF FLEXIBLE MEMBRANE
 EXPANSION JOINT TRIM
 EXPANSION JOINT CLEAT
 1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] @ 24" O.C.

NOTE: REFERENCE TYPICAL TRIM LAP SECTIONS

LOW FLOATING CLIP [HW-230]
 SUPERLOK PANEL

3/8"

MOISTURE BARRIER (NOT BY MBCI)

2 x 4 x 16 GA. ANGLE
 12-11 x 1 PANCAKE HEAD SELF-TAPPER [FASTENER #13A] @ 24" O.C. (PRE-DRILL ANGLE)

LOW RAKE SUPPORT ANGLE [HW-7712]
 1/4-14 x 1 1/4 SHOULDER TEK 2 SELF-DRILLER [FASTENER #5] @ 24" O.C. (CENTER IN SLOT)
 WOOD BLOCKING (NOT BY MBCI)

14-10 x 1 "TYPE A" SELF-TAPPER W/WASHER [FASTENER #18] (2) PER CLIP
 5/8" PLYWOOD MIN. (NOT BY MBCI)

DIM.