



O/O DIMENSION
(SEE PLAN)

BRICK WALL
(NOT BY MBCI)

FIELD SAWCUT

CONT. URETHANE SEALANT
[HW-54_]

COUNTERFLASH [FL-341]

PARAPET HIGH EAVE TRIM
[FL-275]

TRI-BEAD TAPE SEALER
[HW-504]

14-10 x 2 DECK SCREW
[FASTENER #209] @ 24" O.C.
(PRE-DRILL)

URETHANE SEALANT [HW-54_] @ CLOSURE ENDS/PANEL RIB & LAPPING CLOSURE TABS TO SEAL ALL VOIDS

1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] SPACED 1 1/2" FROM PANEL SEAMS, W/ INTERIOR FASTENERS CENTERED OVER MINOR RIBS (7" O.C. MAX.) (NO FASTENER @ PANEL SEAM)

TRI-BEAD TAPE SEALER [HW-504]

LOW SLIDING CLIP [HW-2122]

1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] (3) PER PANEL

METAL OUTSIDE CLOSURE [HW-430] 24" PANEL [HW-432] 18" PANEL [HW-442] 12" PANEL

BACK-UP PLATE [HW-7760] 24" PANEL [HW-7769] 18" PANEL [HW-7761] 12" PANEL

TRI-BEAD TAPE SEALER [HW-504] CONT. ACROSS PANEL

1/4-14 x 5/8 LONG-LIFE 'TYPE B' SELF-TAPPER W/WASHER [FASTENER #46] @ PRE-PUNCHED HOLES (6) PER 24" PANEL (5) PER 18" PANEL (4) PER 12" PANEL

DOUBLE-LOK PANEL

12

2"

3/8"

MOISTURE BARRIER (NOT BY MBCI)

5/8" PLYWOOD MIN. (NOT BY MBCI)

14-10 x 1 'TYPE A' SELF-TAPPER W/WASHER [FASTENER #18] (2) PER CLIP

NOTE:
REFERENCE TYPICAL TRIM LAP SECTIONS

6"

2"