



HIGH EAVE SEALANT DETAIL

O/O DIMENSION
(SEE PLAN)

- MASONRY WALL (NOT BY MBCI)
- URETHANE TUBE SEALANT CONTINUOUS
- COUNTERFLASH [FL-341]
- PARAPET HIGH EAVE TRIM [FL-276]
- FIELD SAWCUT
- TRI-BEAD TAPE SEALER [HW-504] EA. SIDE OF FLEXIBLE MEMBRANE
- 14-10 x 2 DECK SCREW [FASTENER #209] @ 24" O.C. (PRE-DRILL HOLE)

- 1/4-14 x 7/8 LONG-LIFE LAPTEK W/WASHER [FASTENER #4] @ 6" O.C. (DO NOT INSTALL THRU PANEL RIB)
- TRI-BEAD TAPE SEALER [HW-504] @ TOP OF CLOSURE & TOP OF FLEXIBLE MEMBRANE

- OUTSIDE CLOSURE [HW-440] @ 16" PANEL [HW-446] @ 12" PANEL

- FLEXIBLE MEMBRANE
- URETHANE TUBE SEALANT @ CLOSURE ENDS/PANEL RIB & LAPPING CLOSURE TABS TO SEAL ALL VOIDS

- 1/4-14 x 1 1/4 LONG-LIFE SELF-DRILLER W/WASHER [FASTENER #1E] (1) PER RIB

- TRI-BEAD TAPE SEALER [HW-504]

NOTE:
REFERENCE TYPICAL TRIM LAP SECTIONS

- 12
- BATTENLOK HS PANEL

- MOISTURE BARRIER (NOT BY MBCI)
- 5/8" PLYWOOD MIN. (NOT BY MBCI)

- 14-10 x 1 'TYPE A' SELF-TAPPER W/WASHER [FASTENER #18] (4) PER 16" PANEL (3) PER 12" PANEL

2"

2"