



NOTE:  
REFERENCE TYPICAL TRIM  
LAP SECTIONS

TRI-BEAD TAPE SEALER  
[HW-504]  
LOW SLIDING CLIP  
[HW-2122]  
DOUBLE-LOK PANEL

URETHANE SEALANT [HW-54\_]  
@ CLOSURE ENDS (1/4" BEAD MIN.)  
1/4-14 x 7/8 LONG-LIFE LAPTEK  
W/WASHER [FASTENER #4] @ 6" O.C.  
ZEE CLOSURE [FL-360]  
(FIELD CUT TO LENGTH &  
BEVEL CUT TO FIT PANEL)

3 x 3 x 16 GA. BACK-UP  
ANGLE  
8 x 5/8 NIBBED DRILLER  
[FASTENER #24]  
@ 4" O.C.  
TRI-BEAD TAPE SEALER [HW-504]  
CONT. ACROSS PANEL

BEARING PLATE  
[HW-7500]  
METAL DECK  
(MIN. GAUGE THICKNESS)  
(NOT BY MBCI)  
14-10 x \_\_\_\_ DECK  
SCREW [FASTENER #15\_] (2) PER CLIP  
(MIN. 3/4" PENETRATION  
INTO METAL DECK)

RIGID INSULATION  
(NOT BY MBCI)  
VAPOR BARRIER  
(NOT BY MBCI)