



O/O DIMENSION  
(SEE PLAN)

MASONRY WALL (NOT BY MBCI)

URETHANE TUBE SEALANT  
CONTINUOUS  
COUNTERFLASH [T-5225]

FIELD SAWCUT

TRI-BEAD TAPE SEALER [HW-504]  
EA. SIDE OF FLEXIBLE MEMBRANE

14-10 x 2 DECK SCREW  
[FASTENER #209] @ 24" O.C.  
(PRE-DRILL HOLE)

1/4-14 x 7/8 LONG-LIFE LAPTEK  
W/WASHER [FASTENER #4] @ 6" O.C.  
(DO NOT INSTALL THRU PANEL RIB)

TRI-BEAD TAPE SEALER [HW-504]  
@ TOP OF CLOSURE & TOP OF  
FLEXIBLE MEMBRANE

PARAPET HIGH EAVE TRIM

ZEE CLOSURE [T-5014]  
(FIELD CUT TO FIT PANEL)

TRI-BEAD TAPE SEALER  
[HW-504]

FLEXIBLE MEMBRANE

URETHANE TUBE SEALANT  
@ CLOSURE ENDS

1 3/4 x 2 1/4 x 16 GA.  
BACK-UP ANGLE

1/8 x 3/8 POP RIVET  
[FASTENER #14A]  
@ 6" O.C.

12

LOKSEAM PANEL  
MOISTURE BARRIER  
(NOT BY MBCI)

5/8" PLYWOOD MIN.  
(NOT BY MBCI)

UL90 CLIP [HW-6400]  
12-11 x 1 PANCAKE HEAD  
SELF-TAPPER [FASTENER #13A]  
(2) PER CLIP

9"

NOTE:  
REFERENCE TYPICAL TRIM  
LAP SECTIONS